




NUP BEARING LTD

30 mm x 62 mm x 16 mm skf 6206-ZNR Deep groove ball bearings

Bearing No. 6206-ZNR



6206-ZNR Bearing 2D drawings and 3D CAD models

Size	30x62x16 mm
Bore Diameter	30 mm
Outer Diameter	62 mm
Width	16 mm
d	30 mm
D	62 mm
B	16 mm
C	16 mm
b	1,9 mm
d1	40,3 mm
f	1,7 mm
r0 max.	0,6 mm
r1 min.	1 mm
r2 min.	1 mm
C	3,28 mm
D2	54,1 mm
D3	59,61 mm
D4	67,7 mm
ba min.	4,98 mm
Ca max.	4,98 mm
da min.	2,2 mm
da max	40,3 mm
Da max.	56,4 mm
Db min.	69 mm
ra max.	1 mm



NUP BEARING LTD

Weight	0,21 Kg
Basic dynamic load rating (C)	20,3 kN
Basic static load rating (C0)	11,2 kN
Fatigue load limit (Pu)	0,475
Reference speed	24000 r/min
Limiting speed	15000 r/min
Calculation factor (f0)	14
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.213
EAN	7316571402130
Product Group	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68



NUP BEARING LTD

Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6206 ZNRJEM
Weight / LBS	0.48
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
Bore	1.181 Inch 30 Millimeter
d_1	40.36 mm
D_2	54.06 mm
D_3	59.61 mm
D_4	67.7 mm
r_0 max.	0.6 mm
$r_{1,2}$ min.	1 mm
d_a min.	35.6 mm
d_a max.	40.3 mm
D_a max.	56.4 mm
D_b min.	69 mm
b_a min.	2.2 mm
C_a max.	4.98 mm
r_a max.	1 mm
Basic dynamic load rating C	20.3 kN
Basic static load rating C_0	11.2 kN
Fatigue load limit P_u	0.475 kN
Calculation factor k_r	0.025
Calculation factor f_0	14
Mass bearing	0.21 kg
Snap ring	SP 62