




NUP BEARING LTD



skf SAW 23518 x 3.1/4 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAW 23518 x 3.1/4 TLC

SAW 23518 x 3.1/4 TLC Bearing 2D drawings and 3D CAD models

d_a	82.55 mm
D_a	160 mm
C_a	62.23 mm
A_1	98.425 mm
A_2	41.275 mm
S	4.763 mm
b_a	47.625 mm
H	192.484 mm
H_1	101.6 mm
H_2	47.625 mm
J min.	263.525 mm
J max.	295.275 mm
J_1	53.975 mm
L	349.25 mm
N_1	19.05 mm
R_1	60.325 mm
R_2	27.781 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	38.1 mm
Housing	SAW 518
Bearing	23218 CCK/W33
Stabilizing ring	SR-18-15
Labyrinth ring	2 x LOR 189
PosiTrac Plus contact element	2 x B10724-188



NUP BEARING LTD

End plug (suffix Y)	EPR 11
Max. speed for PosiTrac Plus seal	1800 r/min
P _{60°}	101 kN
P _{90°}	60.9 kN
P _{120°}	38.3 kN
P _{150°}	34.7 kN
P _{180°}	42.3 kN
P _a	14.1 kN
Mass pillow block	23.1 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.625 in
Initial grease fill	141.75 g