




NUP BEARING LTD



skf SAF 1522 x 3.7/8 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAF 1522 x 3.7/8 TLC

SAF 1522 x 3.7/8 TLC Bearing 2D drawings and 3D CAD models

d_a	98.425 mm
D_a	200 mm
C_a	62.789 mm
A_1	120.65 mm
A_2	165.1 mm
b_a	42.069 mm
H	239.316 mm
H_1	125.425 mm
H_2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J_1	69.85 mm
L	419.1 mm
N_1	22.225 mm
R_1	67.866 mm
R_2	31.75 mm
R_G	3/8 NPT
P_G	1/4 NPT
h	45.244 mm
Housing	SAF 522
Stabilizing ring	2 x SR-1522
Labyrinth ring	2 x LOR 108
PosiTrac Plus contact element	2 x B10724-109
End plug (suffix Y)	EPR 13
Max. speed for PosiTrac	1450 r/min



NUP BEARING LTD

Plus seal	
P _{60°}	149 kN
P _{90°}	89 kN
P _{120°}	55.6 kN
P _{150°}	50.7 kN
P _{180°}	60.9 kN
P _a	12.5 kN
Mass pillow block	33.1 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g