




NUP BEARING LTD



skf SSAFS 22517 TLC SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22517 TLC

SSAFS 22517 TLC Bearing 2D drawings and 3D CAD models

d_a	74.612 mm
D_a	150 mm
C_a	45.796 mm
A_1	88.9 mm
A_2	127 mm
S	4.763 mm
b_a	35.719 mm
H	187.325 mm
H_1	95.25 mm
H_2	38.1 mm
L	330.2 mm
R_1	53.975 mm
R_2	22.225 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	34.925 mm
Housing	SSAFS 517
Bearing	22217 EK
Adapter sleeve assembly	SNW 17x2.15/16
Stabilizing ring	SR-17-14
Labyrinth ring	2 x LOR 53
PosiTrac Plus contact element	2 x B10724-53
End plug (suffix Y)	EPR 9
Max. speed for PosiTrac Plus seal	1950 r/min



NUP BEARING LTD

P _{60°}	78.7 kN
P _{90°}	47.2 kN
P _{120°}	28.9 kN
P _{150°}	26.7 kN
P _{180°}	32 kN
P _a	9.25 kN
Mass pillow block	24.9 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Initial grease fill	110.56 g