




NUP BEARING LTD



skf SAFS 23056 KA x 10.7/16 SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SAFS 23056 KA x 10.7/16

SAFS 23056 KA x 10.7/16 Bearing 2D drawings and 3D CAD models

d_a	265.113 mm
D_a	419.999 mm
C_a	147.803 mm
A_1	228.6 mm
A_2	317.5 mm
b_a	100.806 mm
H	495.3 mm
H_1	250.825 mm
H_2	101.6 mm
$J_{min.}$	666.75 mm
$J_{max.}$	749.3 mm
J_1	139.7 mm
L	869.95 mm
N_1	41.275 mm
R_1	163.512 mm
R_2	50.8 mm
R_G	1 NPT
P_G	1/4 NPT
h	73.025 mm
Housing	SAFS 056 KAUA
Stabilizing ring	2 x A8819
Labyrinth ring	2 x LOR 606
End plug (suffix Y)	X-5217-2
Bearing limiting speed	1600 r/min
P_{60°	669 kN



NUP BEARING LTD

P_{90°	400 kN
P_{120°	249 kN
P_{150°	222 kN
P_{180°	267 kN
P_a	89 kN
Mass pillow block	382 kg
Cap bolt	4 x 1 1/2-6 UNC
Cap bolt recommended tightening torque	4284.4 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	3515.4 g