




NUP BEARING LTD



skf SSAFS 22524 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. SSAFS 22524 T

SSAFS 22524 T Bearing 2D drawings and 3D CAD models

d_a	106.362 mm
D_a	215.001 mm
C_a	67.793 mm
A_1	120.65 mm
A_2	250.825 mm
S	4.763 mm
b_a	53.181 mm
H	257.175 mm
H_1	133.35 mm
H_2	53.975 mm
L	419.1 mm
R_1	79.375 mm
R_2	30.163 mm
R_G	1/2 NPT
P_G	1/4 NPT
h	46.831 mm
Housing	SSAFS 524
Stabilizing ring	SR-24-20
Taconite seal	TER 113
End plug (suffix Y)	EPR 14
Max. speed for Taconite seal	725 r/min
P_{60°	249 kN
P_{90°	149 kN
P_{120°	94.3 kN
P_{150°	87.2 kN



NUP BEARING LTD

P_{180°	107 kN
P_a	20.7 kN
Mass pillow block	64 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Initial grease fill	379.89 g